

Heavy-Duty, Commercial Grade 1

# DELAYED EGRESS EXIT DEVICE

with Alarm



**FEATURES**

Designed for use on delayed exit applications and ideal for controlled access areas.

**FEATURES:**

- Control to Exit
- Nuisance Alarm
- Momentary Exit
- LED Indicator Modes
- Anti-Disassembly Mode
- Internal Alarm Horn
- Remote Alarm
- Fire Alarm Input
- Definable Delay Time

**STANDARD FEATURES**

<b>Performance</b>	Complies with ANSI A156.3, 2001, Grade 1, UL/ULC Listed
<b>Rail</b>	Fits 30" to 36" doors
<b>Latch Bolt</b>	Stainless steel 3/4" throw with deadlatch feature
<b>Backset</b>	2-3/4"
<b>Strike</b>	Adjustable with slotted holes for adjustments
<b>Cylinder</b>	Standard Schlage (SCC) - 6-pin solid brass, C keyway, keyed different (KD)
<b>Fasteners</b>	Accommodates wood or metal doors with thru bolts standard
<b>Door Range</b>	1-3/4" to 2-1/4" thick
	Surface mounted and covers 161 prep
<b>UL Listed</b>	Fire Rated device available for use on doors rated up to 3 hours
<b>Warranty</b>	Limited lifetime for device; 1 year for electronics

**ALARM FEATURES**

<b>Hardware</b>	<b>CPU</b>	16 bit
	<b>Keypad</b>	Status switch (up/mid/down) x1
	<b>Input ports</b>	Alarm trigger input x1, tamper detection input x1
	<b>Led Indicator</b>	Led status indicator (red/green/blue) x1
	<b>Beep Tone</b>	103 dB Piezo horn
<b>Electrical Condition</b>	<b>Operating Voltage</b>	12VDC Regulated
	<b>Power Consumption</b>	20uA for Standby, Alarm Trigger 83mA
<b>Environmental</b>	<b>Operating Temperature</b>	-10°C - 50°C / 14 °F - 122° F
	<b>Power Consumption</b>	20uA for Standby, Alarm Trigger 83mA

**KEYING OPTIONS FOR SELECT TRIM**

<b>Tell Cylinder</b>	Restricted Tell keyway cylinder can key both the cylinder and interchangeable (IC) core in one lock. The cylinders and cores are interchangeable. Tell keyway cylinder is available only keyed to 6-pin.
----------------------	--

**REQUIRED ACCESSORIES\***

- A regulated power supply with a fire alarm interface. 1 Amp min. @12VDC/set
- Standard electric hinge with the size of 4-1/2" x 4-1/2" or 4-1/2" x 5"; Conductor: 8 conductors

\*Not furnished, order separately

**ESCUTCHEON TRIM**

ITEM	DESCRIPTION	FINISH
EX100342	ESC Entry Escutcheon Lever Trim	US32D/304
EX100343	ESC Entry Escutcheon Lever Trim	US32D/316

