

Standard-Duty Cylindrical Grade 2 Interconnected
LC2700 SERIES



FEATURES

- Performance**
- Complies with ANSI A156.2, Series 4000
 - Grade 2, (400,000 cycles)
 - UL/ULC listed for 3 hour fire door
 - American Disabilities Act (ADA) ANSI A117.1

- Chassis**
- Cylindrical
 - Steel - coated with zinc dichromate (corrosion resistance)

- Lever**
- Non-handed

- Latch**
- 2 3/4" Backset
 - 3/4" Housing diameter
 - 1/2" Stainless steel throw
 - 1 1/8" x 2 1/4" Square corner faceplate

- Strike**
- ASA Strike 1 1/4" x 4 7/8"

- Cylinder**
- C keyway (SCC)
 - 6-pin solid brass
 - Keyed different (KD)

- Keys**
- Two nickel silver per lock cylinder

- Door Thickness**
- 1 3/8" – 1 3/4"

- Door Preparation**
- 2 1/8" diameter
 - 1" diameter for latchbolt
 - Fits standard 161 door prep, 4" centers.

- Warranty**
- Lifetime limited

LC2700 SERIES

OPTIONS

KEYING 6-pin cylinders, can be pinned to 5-pin.


Cylinders Arrow A (ARA), Corbin 59A1 (C059A1), Corbin 60 (C06), Corbin Russwin L4 (CL4), Options Kwikset (KW1), Russwin D1 (RD1), Sargent LA (SAL), Schlage E (SCE), Schlage F (SCF), Weiser E (WRE), Yale 8 (YA8), Yale GA (YGA)

Tell Cylinder Restricted Tell keyway cylinder available, optional. Tell keyway cylinder is available only keyed to 6-pin.


Keying Options Grand master key (GMK), construction master key (CMK), master key (MK), keyed different (KD), keyed alike (KA), interchangeable core uncombined (IC), 0-bitted (OBIT)

AVAILABLE FUNCTIONS Entry 95

LEVER STYLES



Cortland (CTL)



Sturdee (STR)

TELL FINISHES



US32D
Satin Stainless Steel